



PRODUCT SPECIFICATIONS

ThermoTube® Type SL-HT, HTX & HTX2

Pre-Insulated Tubing For High Process Exposure Temperatures

APPLICATION

For Transport of High Temperature Steam or Liquids

ThermoTube Pre-Insulated Tubing HT, HTX and HTX2 are non-heated tube bundles to transport high temperature steam / liquids or for sample lines and impulse lines to pressure instruments. These products are used where heat tracing is deemed unnecessary such as indoors or in climates that do not experience subfreezing temperatures. They limit heat losses for energy conservation and provide personnel protection by limiting outer jacket temperatures.

High temperature ThermoTube pre-insulated tubing bundles are offered in three popular configurations, ranging from 399°C service to continuous operation at 593°C.

RATINGS/SPECIFICATIONS

High Temperature Option:	-HT	-HTX	-HTX2
Service Temperature	399°C	593°C	593°C Intermittent*
Nominal Bundle Diameter	76 mm	89 mm	58 mm
Minimum Bend Radius	406 mm	508 mm	305 mm

* Intermittent exposure is up to 2 minutes per cycle.

PRODUCT FEATURES


- "Touch Safe" Jackets Protect Personnel
- "Cut-to-Length" Coils for Fast Installation
- Conserves Energy

HOW TO SPECIFY

SL-4F1 65 - ATP - HTX

Bundle Type SL = Single Tube	Tube O.D. 2 = 1/4" 3 = 3/8" 4 = 1/2"	Tube Material A = 316 SS Welded D = Monel ¹ E = Titanium F = 316 SS Seamless G = 304 SS Welded H = 304 SS Seamless J = Alloy C276 K = Alloy 825 L = Alloy 20 X = Special	Tube 1	Tube Wall Thickness 35 = .035" 49 = .049" 65 = .065" 83 = .083"	Jacket Option Type ATP ² TPU	HT = 399°C Continuous HTX = 593°C Continuous HTX2 = 593°C Intermittent Exposure
--	--	--	------------------	--	--	---

Notes . . .
 1. Monel is a trademark of Inco Alloys International, Inc.
 2. Black ATP is standard:



CONSTRUCTION

- 1 Process Tube
- 2 High Temperature Woven Glass Fiber Thermal Insulation
- 3 Thermal Diffusion Foil
- 4 Heat Reflective Foil
- 5 Non-hygroscopic Glass Fiber Insulation
- 6 Polymer Outer Jacket (ATP or TPU)

BASIC ACCESSORIES

END SEAL KIT FAK-SSHTX2-SL

- Up to 3.0" o.d.
- Single tube, no tracer
- For SL-HTX2

FAK-SSHT/HTX-2

- Up to 3.50" o.d.
- Single tube, no tracer
- For SL-HT and SL-HTX



THERMON The Heat Tracing Specialists®

tce Thermal Controls and Electronics

TC-E B.V.
Nieuwland Parc 314c
2952 DD Alblasserdam
The Netherlands

+31 (0) 183 20 10 88
sales@tc-e.nl
www.tc-e.nl - www.heattrace.eu
Authorized Thermon distributor